

Hydrodrip

Thin-Medium Wall Drip Line



Specifications

Diameter and wall thickness:

16 mm - ID 15.2 mm:
WT - 18, 25 mil

16 mm - ID 16.1 mm:
WT - 10, 12, 15 mil

22 mm - ID 22.2 mm:
WT - 10, 12, 15, 18, 25 mil

25 mm - ID 25 mm:
WT - 15 mil

Recommended operating pressure:
1.0 bar

Maximum operating pressure according
to wall thickness (See product
specifications below).

Flow rates at 1.0 bar for wall thickness
15 mil: 0.8, 1.2, 1.6, 2.1 lph
(Flow rates vary according to wall
thickness)

Hydrodrip can be ordered at any pre-set
emitter spacing from 20 cm and up.

Applications: For vegetables, annual
field crops, surface and subsurface drip
irrigation

Outlet types:
10-15 mil: Flap or Hole
18-25: Hole

The Hydrodrip thin-medium wall thickness drip line is made with a injection molded dripper which produces excellent uniformity.

Hydrodrip Drip Line is an economical solution for annual row crops, field crops, and greenhouses. Engineered with an efficient turbulent flow path, the Hydrodrip's labyrinth design minimizes clogging.

Hydrodrip is a good choice for manual or mechanized layout, retrieval and suitable for SDI applications. It is available in several diameters, wall thicknesses, dripper spacings and flow rates to meet the needs of your crop.

And with its flap outlet, Hydrodrip Drip Line reduces the ingestion of soil on system shut-down when used in a subsurface application.

Hydrodrip Thin-Medium Wall Drip Line

Hydrodrip - Product Specifications

Diameter (mm)	Flow Rate (lph)	WT		ID (mm)	Max Pressure (bar)	Roll Length (m)
		(mil)	(mm)			
16	0.8, 1.2 1.6, 2.1	10	0.25	16.1	1.3	2200
	0.8, 1.2 1.6, 2.1	12	0.3		1.8	1700
	0.8, 1.2 1.6, 2.1	15	0.38		2.2	1300
	0.8, 1.2 1.65, 2.1	18	0.45	15.2	2.2	1500
	1.3, 1.7 2.2	25	0.6		2.5	800
22	0.8, 1.2 1.6, 2.1	10	0.25	22.2	1.2	1500
	0.8, 1.2 1.6, 2.1	12	0.3		1.4	1100
	0.8, 1.2 1.6, 2.1	15	0.38		1.8	900
	0.8, 1.2 1.65, 2.1	18	0.45		2.0	900
	1.3, 1.7 2.2	25	0.6		2.5	700
25	0.8, 1.2 1.6, 2.1	15	0.38	25	1.4	750



Maximum Drip Line Run (m) on Flat Terrain Flow Variation: EU 90%*

Flow Rate (lph)**	Diameter/Wall Thickness (mm/mil)	Inside Diameter (mm)	Spacing between Emitters (cm)				
			20	30	33	40	50
0.8	16/10-16/15	16.1	168	225	241	276	322
	16/18	15.2	154	207	221	252	294
	22/10-22/15	22.2	303	404	431	492	571
1.2	16/10-16/15	16.1	130	174	186	212	248
	16/18	15.2	123	164	176	201	234
	22/10-22/12	22.2	238	316	338	385	448
	22/15	22.2	240	319	341	389	452
1.65	16/10-16/15	16.1	108	146	156	178	208
	16/18	15.2	99	132	142	162	189
	22/10-22/12	22.2	199	265	283	322	375
	22/15	22.2	201	268	286	326	379
2.1	16/10-16/15	16.1	88	118	126	144	168
	16/18	15.2	84	112	120	137	160
	22/10-22/12	22.2	153	208	223	256	300
	22/15	22.2	166	221	237	270	314

* Pressure at Drip Line inlet: 1.0-1.2 bar, according to wall thickness

**Flow rates indicated are for drip lines with 15 mil wall thickness.

Flow rates vary according to wall thickness.



Rivulis.com

This literature has been compiled for worldwide circulation and the descriptions, photos, and information are for general purpose use only. Please consult with an irrigation specialist and technical specifications for proper use of products. Because some products are not available in all regions, please contact your local dealer for details. Rivulis Irrigation reserves the right to change specifications and the design of all products without notice.

RIV_DS_Hydrodrip_R6_EN_W18_0380